

# InnoVet<sup>®</sup> VERSA

HIGH FREQUENCY RADIOGRAPHIC SYSTEM



**"THE MOST TRUSTED NAME IN VETERINARY RADIOGRAPHY"**

## INNOVET MEANS INTEGRITY

InnoVet revolutionized veterinary radiography in 1991 with the first x-ray system designed by veterinarians. Since then, InnoVet has manufactured more than 6,000 veterinary x-ray systems, making it the #1 veterinary x-ray manufacturer in the United States.

Add to that, the industry's best warranty and it's no wonder InnoVet is the most trusted name in veterinary radiography.



## LOCAL SUPPORT

Capital equipment is a long-term investment that deserves personal attention from a service professional who understands your practice.

Regional InnoVet dealers are factory-trained to install and service your x-ray systems with immediate on site support. Our trusted support network means image quality will never slow down your practice.

## INDUSTRY BEST WARRANTY

Our 7-year limited parts warranty secures your investment today and guarantees your investment value tomorrow.

# InnoVet®

2901 W. Lawrence Ave. • Chicago, IL 60625  
800-972-9776 • 773-588-2444  
Fax 773-588-3424  
www.innovet4vets.com

## System Specifications

### TABLE / TUBESTAND

- Encased x-ray tube reduces radiation leakage by over 50% providing extraordinary safety
- Unique column and covers safeguard staff and patients from exposed electrical wires
- Rounded corners prevent hip-level bruising common to veterinary technicians
- Table top fluid trough
- Stationary table top: 56 in. x 24 in.

### COLLIMATOR

- Radiation leakage well below Federal standards for human medical systems

### HIGH FREQUENCY GENERATOR

- 20 KHz High Frequency technology
- 30 kW rating
- kVp range: 40 – 125, in 1 kV increments
- mA stations: 50s, 100s, 100L, 300L
- mAs range: 0.2 to 400
- mAs/kVp technique selection
- Automatic generator "Shut Off" circuit
- Adjustable volume, audible exposure signal
- UL classified

### X-RAY TUBE

- 1.0-2.0 mm F.S., 140,000 H.U. with 90° horns

## System Options

- Anatomical programmed technique selection
- 500 mA generator upgrade
- Four-way float top table, 67 in. x 32 in.
- Table top fluid trough
- Storage bin