

# InnoVet<sup>®</sup> VERSA DIGITAL RADIOGRAPHIC SYSTEM DR



**"THE MOST TRUSTED NAME IN VETERINARY RADIOGRAPHY"**

## INNOVET MEANS INTEGRITY

InnoVet revolutionized veterinary radiography in 1991 with the first x-ray system designed by veterinarians. Since then, InnoVet has manufactured more than 6,000 veterinary x-ray systems, making it the #1 veterinary x-ray manufacturer in the United States.

Add to that, the industry's best warranty and it's no wonder InnoVet is the most trusted name in veterinary radiography.



## LOCAL SUPPORT

Capital equipment is a long-term investment that deserves personal attention from a service professional who understands your practice.

Regional InnoVet dealers are factory-trained to install and service your x-ray systems with immediate on-site and remote support. Our trusted support network means image quality will never slow down your practice.

## INDUSTRY BEST WARRANTY

Our 7-year limited parts warranty secures your investment today and guarantees your investment value tomorrow.

# InnoVet®

2901 W. Lawrence Ave. • Chicago, IL 60625  
800-972-9776 • 773-588-2444  
Fax 773-588-3424  
www.innovet4vets.com

## SYSTEM SPECIFICATION

### DIGITAL DETECTOR

- High quality image resolution: 3.5 LP/mm
- Large 17 in. x 17 in. image field (43 cm x 43 cm)
- 9 megapixel array
- Time to image: less than 10 seconds

### SOFTWARE

- User-friendly acquisition and viewing software
- Unlimited viewing licenses
- Share images via DICOM transfer or convert to common formats ( .jpg, .bmp, .dcm, .tiff) and burn them to CD/DVD or e-mail
- Integrates with many Practice Management Softwares

### TABLE / TUBESTAND

- Encased x-ray tube reduces radiation leakage by over 50% providing extraordinary safety
- Unique column and covers safeguard staff and patients from exposed electrical wires
- Rounded corners prevent hip-level bruising common to veterinary technicians
- Stationary table top: 56 in. x 24 in.

### COLLIMATOR

- Radiation leakage meets Federal standards for human medical systems.

### HIGH FREQUENCY GENERATOR

- 20 kHz High Frequency technology
- 30 kW power rating
- kVp range: 40 – 125, 1 kV increments
- mA stations: 50-300
- mAs range: 0.2 to 400
- mAs/kVp technique selection
- Automatic generator "Shut-off" circuit
- Adjustable volume, audible exposure signal
- UL Classified

### X-RAY TUBE

- 1.0-2.0 mm Focal Spots, 140,000 Heat Units

### COMPUTER

- PC with RAID 1 (two 500GB hard drives), 4 GB RAM
- Windows 7 Operating System with XP mode
- 24 inch, 2.3 MP monitor

## SYSTEM OPTIONS

Only pay for the extra features you select:

- Anatomical programming upgrade
- 500 mA generator upgrade (300 mA standard)
- Four-way float table top upgrade 67 in. x 29 in.
- Cesium scintillator upgrade